STEAD & WILKINS

Precision Engineering & Fabrications



Data Sheet 00052

Camera Post

Standard Round Post: Model SAW5014

Standard Square Post: Model SAW5016

Circular Camera Post

All our posts are supplied cut to the height requested, up to a maximum of <u>3M. The standard diameter</u> of the pole is 114.3mm.

Finish:

M24 of RT/CE/C/002.

Acid pickled and hot dipped galvanised to BS EN ISO 1461, thickness 85um

Excess galvanising removed

T-washed – minimum 4 hours dry

2 coat RT98 Interseal 670 surface tolerant epoxy primer DFT: 200µm

1 coat RT98 acrylic urethane finish coat (colour to be specified) DFT:

50µmgalvanised

Standard Round Post - Model SAW5014

The base of this post is 300mm square, 20mm thick with 4 x 26 dia holes pitched at 200mm centres.

Weight 65kgs; Width 300mm; Depth 300mm; Height 3000mm; Circular Hollow Section 114.3mm Weight per M 17Kgs

Variations

Large base - Model SAW5764


The base of this post is 400mm square, 20mm thick with 4 \times 26 dia holes pitched at 300mm centres. Designed to fit on suspended platforms with restricted width.


Weight 75kgs; Width 400mm; Depth 400mm; Height 3000mm Circular Hollow Section 114.3mm Weight per M 17Kgs


Large base - Model SAW5765

The base of this post is 400mm square, 20mm thick with 4 x 26x76mm slots pitched at 300mm centres. Designed to fit on suspended PCC slab platforms.

Weight 75kgs; Width 400mm; Depth 400mm; Height 3000mm Circular Hollow Section 114.3mm Weight per M 17Kgs







SAW5014 SAW5764

SAW5765

Key Features:

Robust construction

Galvanised protection

Cut to length

Variable base arrangements

Square or round section

Square type, hinged

Stead & Wilkins Ltd Jolly Farmers Wharf Thames Road Crayford

Dartford

Kent DA1 40H

Tel: +44 (0)1322 529134 Fax: +44 (0)1322 550314



Certificate FM33624 BS EN ISO 9001:2008



STEAD & WILKINS

Precision Engineering & Fabrications



Data Sheet 00052

Camera Post

Standard Round Post: Model SAW5014

Standard Square Post: Model SAW5016

Square Camera Post

All our posts are supplied cut to the height requested, up to a maximum of 3M. The standard size of this pole is 100mm square.

Finish:

M24 of RT/CE/C/002.

Acid pickled and hot dipped galvanised to BS EN ISO 1461, thickness 85um

Excess galvanising removed

T-washed – minimum 4 hours dry

2 coat RT98 Interseal 670 surface tolerant epoxy primer DFT: 200μm 1 coat RT98 acrylic urethane finish coat (colour to be specified) DFT: 50μmgalvanised

Standard Square Post – Model SAW5016

The square post has been specially designed to offer increased safety, when performing maintenance on the camera housing installations in conduction with overhead power cables. The unit is hinged 1M from platform level and to ease the lowering operation it is fitted with an internal spring arrangement.

Weight 105kgs; Width 300mm; Depth 300mm; Height 3000mm; Square Hollow Section 100mm x 100mm Weight per M 18kgs

Variations

Large base - Model SAW5753


The base of this post is 400mm square, 20mm thick with 4 \times 26 dia holes pitched at 300mm centres. Designed to fit on suspended platforms with restricted width.


Weight 115kgs; Width 400mm; Depth 400mm; Height 3000mm; Square Hollow Section 100mm x 100mm Weight per M 18kgs


Large base – Model SAW5754

The base of this post is 400mm square, 20mm thick with 4 x 26x76mm slots pitched at 300mm centres. Designed to fit on suspended PCC slab platforms.

Weight 115kgs; Width 400mm; Depth 400mm; Height 3000mm; Square Hollow Section 100mm x 100mm Weight per M 18kgs







Key Features:

Robust construction

Galvanised protection

Cut to length

Variable base arrangements

Square or round section

Square type, hinged

Stead & Wilkins Ltd Jolly Farmers Wharf Thames Road Crayford

Dartford

Kent DA1 40H

Tel: +44 (0)1322 529134 Fax: +44 (0)1322 550314



Certificate FM33624 BS EN ISO 9001:2008



STEAD & WILKINS

Precision Engineering & Fabrications



Data Sheet 00052

Camera Post

Standard Round Post: Model SAW5014

Standard Square Post: Model SAW5016

Accessories available for the Camera posts, new or original

SAW5756 - Round to round adaptor 400: 275 to increase the length of the post by 400mm and in conduction with a short off-set arm.

Weight 7.5kgs; Width 110mm; Depth 110mm; Height 683mm;

SAW5755 - Round to round adaptor 400: 400 to increase the length of the post by 400mm and in conduction with a longer off-set arm.

Weight 10kgs; Width 110mm; Depth 110mm; Height 808mm;

SAW5016/6 - Cable gland interface, for holding retaining glands, power and signal, at the top of the camera post.



SAW5016/6 - Square to round adaptor 25:275 to enable the square camera post, SAW 5016 to be used the standard off-set arms, SAW5884.

SAW5014



SAW5016



Key Features:

Robust construction

Galvanised protection

Cut to length

Variable base arrangements

Square or round section

Square type, hinged

Stead & Wilkins Ltd Jolly Farmers Wharf Thames Road Crayford Dartford

Kent

DA1 4QH

Tel: +44 (0)1322 529134 Fax: +44 (0)1322 550314



Certificate FM33624 BS EN ISO 9001:2008

